Brushing Liquid 333

Thinners & Solvents





PRODUCT DESCRIPTION

Brushing Liquid 333 is a slow drying solvent to ease brushing and facilitate the flow of specified paint coatings. Extends drying in hot weather.

* For use with specified topside paints

PRODUCT INFORMATION

 Colour
 Y333-Clear

 Specific Gravity
 0.8

 Volume Solids
 0%

 Typical Shelf Life
 3 yrs

 VOC (As Supplied)
 805 g/lt

Unit Size 1 US Pint, 1 US Quart, 1 US Gallon

Thinners to improve flow of enamels, varnishes and Brightside

DRYING/OVERCOATING INFORMATION

Drying

Overcoating Substrate Temperature

5°C (41°F) 10°C (50°F) 23°C (73°F) 35°C (95°F)
Min Max Min Max Min Max Min Max Min Max

APPLICATION AND USE

Overcoated By

Method Add small increments, in accordance with individual product directions.

Compatibility/Substrates Compatible with specified topside paints including Brightside, enamels and varnishes

TRANSPORTATION, STORAGE AND SAFETY INFORMATION

Storage TRANSPORTATION:

Brushing Liquid 333 should be kept in securely closed containers during transport and storage.

STORAGE

Exposure to air and extremes of temperature should be avoided. For the full shelf life of Brushing Liquid 333 to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight.

Keep out of direct sunligh

Safety DISPOSAL

Container Disposal: Triple Rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in

a sanitary landfill or by other procedures approved by state or local authorities.

GENERAL:

Read the label safety section for Health and Safety Information, also available from our Technical Help Line.

IMPORTANT NOTESThe performance of any marine paint or coating depends on many factors outside the control of International Paint

LLC., including surface preparation, proper application, and environmental conditions. Therefore, International Paint LLC. cannot guarantee this product's suitability for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND/OR MERCHANTABILITY ARE EXCEEDED. International Paint Inc. SHALL NOT, UNDER ANY CIRCUMSTANCES, BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase of this product, the buyer agrees that the sole exclusive remedy, if any, is limited to the refund of the

purchase price or replacement of the product at International Paint LLC. option.