

# Brushing Thinner No.6

## Thinners & Solvents

### Brushing Thinner



#### PRODUCT DESCRIPTION

A formulated product to assist users when brushing Brightside® or Goldspar®.

- \* Allows for a long "wet edge" time
- \* Improves feel of paint under the brush
- \* Does not affect any durability, flexibility or toughness properties of product it is added into

#### PRODUCT INFORMATION

Colour	YTA066
Volume Solids	0%
Typical Shelf Life	2 yrs
Unit Size	250 ml

#### DRYING/OVERCOATING INFORMATION

##### Drying

##### Overcoating Substrate Temperature

Overcoated By	5°C (41°F)		10°C (50°F)		23°C (73°F)		35°C (95°F)	
	Min	Max	Min	Max	Min	Max	Min	Max

#### APPLICATION AND USE

<b>Method</b>	Stir into product and apply by brush and/or roller.
<b>Hints</b>	<b>Thinning</b> Level of addition for Brightside and Goldspar is typically up to a maximum level of 10% by volume. As a general guide the following addition levels should be used: 18-22°C - Up to 5%; 22-25°C - 5-7.5%; 25-30°C - 7.5-10%. Users should evaluate the levels required for their conditions. <b>Ventilation and Humidity Control</b> Ensure adequate ventilation during use. <b>Other</b> Using this product will generally reduce the film build obtained with each coat. With some reds, yellows and oranges extra coats may be required to obtain opacity. As an aid to obtaining full opacity the last coat of undercoat may be mixed with Brightside typically 50/50 before application. Keeping the substrate cool and painting out of the wind and/or direct sun will improve conditions for painting dramatically.
<b>Some Important Points</b>	Product temperature should be minimum 18°C and maximum 30°C. Ambient temperature should be minimum 18°C and maximum 30°C. Substrate temperature should be minimum 18°C and maximum 25°C. Product may be used at higher temperatures but obviously above 30°C it becomes difficult to control application properties of any paint. Although this material will still improve wet edge the overall finish may still be compromised. At temperatures lower than 18°C the product may be used but note that dust pick up times may be extended considerably and the propensity for product to run will be greater.
<b>Compatibility/Substrates</b>	Compatible with Brightside® and Goldspar®.

#### TRANSPORTATION, STORAGE AND SAFETY INFORMATION

<b>Storage</b>	<b>TRANSPORTATION:</b> Brushing Thinner No.6 should be kept in securely closed containers during transport and storage. <b>STORAGE:</b> Exposure to air and extremes of temperature should be avoided. For the full shelf life of Brushing Thinner No.6 to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight.
<b>Safety</b>	<b>DISPOSAL:</b> Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. <b>GENERAL:</b> Read the label safety section for Health and Safety Information, also available from our Technical Help Line. Always use gloves and goggles and keep skin protected with overalls. Users should ensure they have a copy of the Material Safety Datasheet for this product and that they are familiar with all the safety directions before use.
<b>IMPORTANT NOTES</b>	<i>The technical information and suggestions for use and application presented herein are not intended to be exhaustive, but they represent the best information available to use and are believed to be reliable. They should not, however, be construed as controlling suggestions and there is no warranty of performance of our materials either expressed or implied. We urge that users of our materials conduct confirmatory tests to determine final suitability for their specific</i>

Please refer to your local representative or visit <http://www.yachtpaint.com> for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2014.

Brushing Thinner No.6  
Thinners & Solvents  
Brushing Thinner



---

*end uses. Because this datasheet is subject to changes from time to time, it is the user's responsibility to check that this sheet is current prior to using the product.*

---

Please refer to your local representative or visit <http://www.yachtpaint.com> for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2014.

Ref:3208 Brushing Thinner No.6 Issue Date:15/12/2014