Thinner No.16 Thinners & Solvents



PRODUCT DESCRIPTION

This product is a blend of organic solvents specifically designed for thinning and/or equipment cleaning in association with Interior Finish.

PRODUCT INFORMATION

 Colour
 ITA070

 Specific Gravity
 0.86

 Volume Solids
 0%

 Typical Shelf Life
 2 yrs

 VOC (As Supplied)
 859 g/lt

 Unit Size
 5 Lt

DRYING/OVERCOATING INFORMATION

Drying

Overcoating Substrate Temperature

Min

Max

5°C (41°F) 10°C (50°F) 23°C (73°F)

Max

Min

35°C (95°F) Min Max

Overcoated By

APPLICATION AND USE

Hints Ventilation and Humidity Control Ensure adequate ventilation during use.

Some Important Points No special restrictions.

TRANSPORTATION, STORAGE AND SAFETY INFORMATION

Storage GENERAL INFORMATION:

Exposure to air and extremes of temperature should be avoided. For the full shelf life of this product to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight.

TRANSPORTATION:

Min

The product should be kept in securely closed containers during transport and storage.

Safety GENERAL: Read the label safety section for Health and Safety Information, also available from our Technical Help Line.

DISPOSAL: Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to

harden before disposal.

Remainders of Thinner No.16 cannot be disposed of through the municipal waste route or dumped without permit.

Disposal of remainders must be arranged for in consultation with the authorities.

IMPORTANT NOTESThe information given in this sheet is not intended to be exhaustive. Any person using the product without first making

further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal interpretability for the performance) arising a total formation of the performance of the product of the performance of the performance of the product of the performance of

injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.