

Safety Data Sheet
INTERFIL 830 BASE



Bulk Sales Reference No.:
SDS Revision Date:
SDS Revision Number:

Sales
Order: {SalesOrd}
YAA867
01/16/2019
E4-6

1. Identification of the preparation and company

1.1. Product identifier

Product Identity INTERFIL 830 BASE
Bulk Sales Reference No. YAA867

1.2. Relevant identified uses of the substance or mixture and uses advised against
Intended Use See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name Akzo Nobel Coatings
Manufacturer:
Akzo Nobel Coatings
International Paint
6001 Antoine Drive
Houston, Texas 77091

Emergency
CHEMTREC (800) 424-9300
International Paint (713) 527-3887
Poison Control Center (800) 854-6813
Customer Service
International Paint (800) 589-1267
Fax No. (800) 631-7481

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Skin Irrit. 2;H315 Causes skin irritation.
Eye Irrit. 2;H319 Causes serious eye irritation.
Skin Sens. 1;H317 May cause an allergic skin reaction.
Aquatic Chronic 2;H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Warning.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P302+352 IF ON SKIN: Wash with soap and water.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P333+313 If skin irritation or a rash occurs: Get medical advice/attention.

P337 If eye irritation persists:.

P362 Take off contaminated clothing and wash before reuse.

P363 Wash contaminated clothing before reuse.

P391 Collect spillage.

P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating Health: 2 Flammability: 2 Reactivity: 0

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

| Ingredient/Chemical Designations | Weight % | GHS Classification | Notes |
|---|----------|--|-------|
| Bisphenol A - Epichlorohydrin polymer CAS Number: 0025068-38-6 | 25 - 50 | Eye Irrit. 2;H319 Skin Irrit. 2;H315 Skin Sens. 1;H317 Aquatic Chronic 2;H411 | [1] |
| Bisphenol F epoxy resin CAS Number: 0028064-14-4 | 25 - 50 | Skin Irrit. 2;H315 Eye Irrit. 2;H319 Skin Sens. 1;H317 Aquatic Chronic 2;H411 | [1] |
| Borosilicate glass CAS Number: 0065997-17-3 | 1.0 - 10 | Eye Irrit. 2;H319 | [1] |
| Alkyl(C12-C14)glycidyl ether CAS Number: 0068609-97-2 | 1.0 - 10 | Skin Irrit. 2;H315 Skin Sens. 1;H317 | [1] |
| Fillite CAS Number: 0061132-18-1 | 1.0 - 10 | ---- | [1] |
| Silane, trimethoxyoctyl-, hydrolysis products with silica CAS Number: 0092797-60-9 | 1.0 - 10 | ---- | [1] |

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

| | |
|------------|---|
| General | Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes. |
| Inhalation | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately. |
| Eyes | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. |
| Skin | In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately. |
| Ingestion | If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|----------|--|
| Overview | NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. |
|----------|--|

YAA867_E4

| | |
|-----------------|---|
| | Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing. |
| Inhalation | Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea. |
| Eyes | Causes severe eye irritation. Avoid contact with eyes. |
| Skin | Causes skin irritation. May be harmful if absorbed through the skin. |
| Ingestion | Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness. |
| Chronic effects | |

5. Fire-fighting measures

5.1. Extinguishing media

SMALL FIRES: Use dry chemical, CO₂, water spray or foam. LARGE FIRES: Use water spray, fog, or foam. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material.

5.2. Special hazards arising from the substance or mixture

No data available

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 159

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. LARGE SPILLS: Dike far ahead of liquid spill to contain released material and runoff from fire control.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

7. Handling and storage

7.1. Precautions for safe handling

Handling

Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

In Storage

Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Avoid contact with eyes, skin and clothing.

No data available

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

| CAS No. | Ingredient | Source | Value |
|--------------|---|-----------|----------------------|
| 0025068-38-6 | Bisphenol A - Epichlorohydrin polymer | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0028064-14-4 | Bisphenol F epoxy resin | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0061132-18-1 | Fillite | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0065997-17-3 | Borosilicate glass | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0068609-97-2 | Alkyl(C12-C14)glycidyl ether | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0092797-60-9 | Silane, trimethoxyoctyl-, hydrolysis products with silica | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |

Health Data

| CAS No. | Ingredient | Source | Value |
|---------|------------|--------|-------|
|---------|------------|--------|-------|

YAA867_E4

| | | | |
|--------------|---|-------|----------------------|
| 0025068-38-6 | Bisphenol A - Epichlorohydrin polymer | NIOSH | No Established Limit |
| 0028064-14-4 | Bisphenol F epoxy resin | NIOSH | No Established Limit |
| 0061132-18-1 | Fillite | NIOSH | No Established Limit |
| 0065997-17-3 | Borosilicate glass | NIOSH | No Established Limit |
| 0068609-97-2 | Alkyl(C12-C14)glycidyl ether | NIOSH | No Established Limit |
| 0092797-60-9 | Silane, trimethoxyoctyl-, hydrolysis products with silica | NIOSH | No Established Limit |

Carcinogen Data

| CAS No. | Ingredient | Source | Value |
|--------------|---|--------|--|
| 0025068-38-6 | Bisphenol A - Epichlorohydrin polymer | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0028064-14-4 | Bisphenol F epoxy resin | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0061132-18-1 | Fillite | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0065997-17-3 | Borosilicate glass | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0068609-97-2 | Alkyl(C12-C14)glycidyl ether | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0092797-60-9 | Silane, trimethoxyoctyl-, hydrolysis products with silica | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |

8.2. Exposure controls

Respiratory

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.

Eyes

Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

Skin

Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

Engineering Controls

Depending on the site-specific conditions of use, provide adequate ventilation.

Other Work Practices

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of

soap and water.

9. Physical and chemical properties

| | |
|---|--|
| Appearance | Grey Liquid |
| Odor threshold | Not Measured |
| pH | No Established Limit |
| Melting point / freezing point | Not Measured |
| Initial boiling point and boiling range | 80 (°C) 176 (°F) |
| Flash Point | 240 (°C) 464 (°F) |
| Evaporation rate (Ether = 1) | Not Measured |
| Flammability (solid, gas) | Not Applicable |
| Upper/lower flammability or explosive limits | Lower Explosive Limit: 1 Upper Explosive Limit: No Established Limit |
| vapor pressure (Pa) | Not Measured |
| Vapor Density | Heavier than air |
| Specific Gravity | 0.79 |
| Solubility in Water | Not Measured |
| Partition coefficient n-octanol/water (Log Kow) | Not Measured |
| Auto-ignition temperature | Not Measured |
| Decomposition temperature | Not Measured |
| Viscosity (cSt) | No Established Limit Not Measured |
| VOC % | Refer to the Technical Data Sheet or label where information is available. |
| VOHAP content (gm/litre of paint) | 0.00 (as supplied) |
| VOHAP content (gm/litre of Solid Coating) | 0.00 (as supplied) |

10. Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No data available

11. Toxicological information

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapor LC50, mg/L/4hr | Inhalation Dust/Mist LC50, mg/L/4hr |
|--|------------------------------|----------------------------------|---------------------------------|-------------------------------------|
| Bisphenol A - Epichlorohydrin polymer - (25068-38-6) | 5,001.00, Rat - Category: NA | 20,000.00, Rabbit - Category: NA | No data available | No data available |
| Bisphenol F epoxy resin - (28064-14-4) | | | | |

YAA867_E4

| | | | | |
|---|---------------------------------|----------------------|----------------------|-------------------|
| | 2,000.00, Rat - Category: 4 | No data available | No data available | No data available |
| Borosilicate glass - (65997-17-3) | No data available | No data available | No data available | No data available |
| Alkyl(C12-C14)glycidyl ether - (68609-97-2) | No data available | No data available | No data available | No data available |
| Fillite - (61132-18-1) | No data available | No data available | No data available | No data available |
| Silane, trimethoxyoctyl-, hydrolysis products with silica - (92797-60-9) | 5,340.00, Rat - Category: NA | No data available | No data available | No data available |

| Item | Category | Hazard |
|--|----------------|--------------------------------------|
| Acute Toxicity (mouth) | Not Classified | Not Applicable |
| Acute Toxicity (skin) | Not Classified | Not Applicable |
| Acute Toxicity (inhalation) | Not Classified | Not Applicable |
| Skin corrosion/irritation | 2 | Causes skin irritation. |
| Eye damage/irritation | 2 | Causes serious eye irritation. |
| Sensitization (respiratory) | Not Classified | Not Applicable |
| Sensitization (skin) | 1 | May cause an allergic skin reaction. |
| Germ toxicity | Not Classified | Not Applicable |
| Carcinogenicity | Not Classified | Not Applicable |
| Reproductive Toxicity | Not Classified | Not Applicable |
| Specific target organ systemic toxicity (single exposure) | Not Classified | Not Applicable |
| Specific target organ systemic Toxicity (repeated exposure) | Not Classified | Not Applicable |
| Aspiration hazard | Not Classified | Not Applicable |

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

| Ingredient | 96 hr LC50 fish, mg/l | 48 hr EC50 crustacea, mg/l | ErC50 algae, mg/l |
|---|------------------------------|-------------------------------|----------------------|
| Bisphenol A - Epichlorohydrin polymer - (25068-38-6) | 3.10, Pimephales promelas | 1.40, Daphnia magna | Not Available |
| Bisphenol F epoxy resin - (28064-14-4) | 9.00, Oncorhynchus mykiss | 9.00, Daphnia magna | Not Available |
| Borosilicate glass - (65997-17-3) | Not Available | Not Available | Not Available |
| Alkyl(C12-C14)glycidyl ether - (68609-97-2) | Not Available | Not Available | Not Available |
| Fillite - (61132-18-1) | Not Available | Not Available | 0.00 (hr), |
| Silane, trimethoxyoctyl-, hydrolysis products with silica - (92797-60-9) | Not Available | Not Available | Not Available |

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

13. Disposal considerations

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

14.1. UN number Not Regulated

14.2. UN proper shipping name Not Regulated

14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation)

Proper Shipping Name Not Regulated

Hazard Class Not Regulated

UN / NA Number Not Regulated

Packing Group Not Regulated

CERCLA/DOT RQ Not Applicable gal. /
Not Applicable lbs.

IMO / IMDG (Ocean Transportation)

IMDG Proper Shipping Name Not Regulated

IMDG Hazard Class Not Regulated
Sub Class Not applicable

IMDG Packing Group Not Regulated

System Reference 9
Code

14.4. Packing group Not Regulated

14.5. Environmental hazards

IMDG Marine Pollutant: Yes (Bisphenol A - Epichlorohydrin polymer)

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification D2B

DOT Marine Pollutants (10%):
(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):
(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%) :
(No Product Ingredients Listed)

EPCRA 302 Extremely Hazardous (>.1%) :
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :
Isopropyl Alcohol

Mass RTK Substances (>1%) :
(No Product Ingredients Listed)

Penn RTK Substances (>1%) :
(No Product Ingredients Listed)

Penn Special Hazardous Substances (>.01%) :
Carbon black

RCRA Status:
(No Product Ingredients Listed)
N.J. RTK Substances (>1%) :
(No Product Ingredients Listed)
N.J. Special Hazardous Substances (>.01%) :
(No Product Ingredients Listed)
Carbon black
Isopropyl Alcohol
N.J. Env. Hazardous Substances (>.1%) :
Isopropyl Alcohol
Proposition 65 - Carcinogens (>0%):
Naphthalene
Ethyl Benzene
Carbon black
Proposition 65 - Female Repro Toxins (>0%):
(No Product Ingredients Listed)
Proposition 65 - Male Repro Toxins (>0%):
(No Product Ingredients Listed)
Proposition 65 - Developmental Toxins (>0%):
(No Product Ingredients Listed)

| |
|-----------------------|
| 16. Other information |
|-----------------------|

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

This is the first revision of this SDS format, changes from previous revision not applicable.

End of Document